

Dependable Timberland Fires Detection Using Wireless Sensor Networks

Rupali Mahajan^a and Dr. Rashmi Priyadarshini^b

^aAssistant Professor, Department of Electronics and Communication Engineering, Hindustan College of Science and Technology, Mathura (Uttar Pradesh) and Research Scholar, SET, Sharda University, Greater Noida (INDIA). Email: rupali_mahajan61@rediffmail.com

^bAssociate Professor, Department of Electrical Electronics and communication Engineering, Sharda University, Greater Noida (INDIA). Email: rashmi.priyadarshini@sharda.ac.in
(Corresponding Author Email: rupali_mahajan61@rediffmail.com)
DOI: 10.47750/pnr.2022.13.508.169

Abstract

The enhancement in the degree of modernization of woodland fires identification involving data and correspondence innovations have key importance for some nations where timberland fires happen as often as possible. Contrasted to the conventional procedures of backwoods fires identification, wireless sensor network (WSN) innovation is an extremely encouraging innovation. Here, a near report between two timberland fires location strategies (Canadian and Korean) utilizing a truly test approach is proposed. The procedure took on is also given in this paper. The connected equipment plots and executed calculations are given exhaustively for the two strategies. Through the fundamental outcomes, we can reason that the Canadian methodology is more viable as far as energy utilization and execution speed.

Keywords: Canadian approach; Korean approach; Timberland fires detection; WSN

1. Introduction

The likelihood of ignition of backwoods is in strong increment owing to environment changes and human exercises. Woods fire not only diminish the swathe of trees but also lead to an expansion in Earth's gas outflow. Around twenty percent of Carbon dioxide emission in climate is because of woodland fire. Roughly thirteen million hectares of woods are annihilated annually on this planet in fires. Traditional woodland fire identification strategies identify fire when it turns out to be huge and truly challenging to put out. Subsequently, wireless sensor network (WSN) innovation should be utilized for recognition of woodland fire in beginning phase to secure the vegetation. For this purpose, various sensor hubs should be pre-conveyed in a timberland that can assemble various sorts of crude information, like temperature, moistness and position. All detected information are sent remotely to a sink station, which then sends information to the central controller through a set-up like GSM, UMTS, Satellite, TCP/IP organizations. This framework should be ongoing, else it will be of no use. Here, an answer in view of WSN is proposed for solid recognition of backwoods fires by utilizing two simultaneous location frameworks: Canadian framework and Korean framework. A relative report on the two frameworks is given here.

Generally, backwoods fires are recognized utilizing customary procedures, for example, monitoring tower situated at high focuses and Osborne fire Finder. Tragically these procedures are wasteful because of human fallibility and troublesome living conditions. This had permitted a few nations to utilize woods fire location frameworks in light of satellite imaging. MODIS (Moderate Resolution Imaging Spectroradiometer) utilized in CANADA and AVHRR (Advanced Very High Resolution Radiometer) utilized in CHINA are satellite-based checking frameworks. Nevertheless these methodologies are shown to be restricted by territory, season and climate. As of late, the innovation of WSN has arisen and has been embraced by a few nations. This innovation considers significant design objectives and rudiments, for example, energy effectiveness, early identification and exact confinement, estimate capacity and versatile to intolerant climate.

2.Literature review

Many exploration works connected to woodland fires by utilizing WSN innovation have been taken place all over the world. B. C. Ko et. al.[1,2] surveyed alert systems for various types of natural disasters such as wildfire smoke and fire identification, water level detection for flood prevention and coastal zone monitoring, using computer vision and pattern-recognition techniques. U. Ganesh et. al.[3] proposed an advanced system for forest fire identification that overcomes the demerits of MODIS. The developed system has two main modules: Monitoring Area Module and Forest Area Module. Michel Owayjan et. al.[4] and Antonio Molina-Pico et. al.[12] featured remote sensor networks as a likely arrangement of early identification of backwoods fires. The gadget utilizes different sensors, sunlight based re-energizing instrument and remote information transmission, to satisfy the errand. The gathered information is communicated to a close to focal unit where it is dissected and afterward transferred to a web-based site that connects public protection division in case essential. The site can be opened by particular experts to make early moves in the event of any alert. Mohamed Kameche et. al.[5] discussed about a constellation of four low earth orbit nanosatellites for disaster monitoring. Kumarguru Poobalan et. al.[6] explained a fire location calculation in light of image processing methods is proposed which is viable in observation gadgets like CCTV, remote camera to UAVs. Sakib Abdullah et. al.[8] talked about another classification of smaller, effectively deployable and energy proficient way to deal with sensor hubs for the continued vigilance of backwoods conditions and location of flames in their early stages in view of a mix of tangible sources of info. The sensor network announced here has been tried with different subsystems, in a genuine firefighting situation and gave promising outcomes. Pradeep Kumar Singh et. al.[9] investigated various well known remote sensor network based woodland fire recognition methods. Gaur, A. et. al.[10] presented an overview of existing state-of-the-art practices in the field of fire sensing and controlling system Panagiotis Barmpoutis et. al.[11] summarized optical remote detecting innovations utilized in early fire notice frameworks and gives a broad overview on both fire and smoke location calculations. Three sorts of frameworks are recognized, in particular earthbound, airborne and space borne-based frameworks. Beatriz Flamia Azevedo et. al.[12] proposed a mathematical model to resolve sensor allocation problem in wireless sensor network.

3.Forest fire detection Methods

Forest fire detection in view of WSN includes three key phases:

1. Information gathering
2. Interactions via net
3. Investigation of gathered information

Information gathering unit: This unit makes it conceivable to catch different climate situations vital for estimation of index; and runs intermittently till occasion of fire happens.

Communication unit: It is utilized to course earnest information (alerts) produced by information gathering unit to investigating unit inside specific boundaries of quality of service (QoS) like unwavering quality (alert should show up at sink securely), worldly limitation (caution should show up inside a sensible time) and security (directing way taken by alert should be safe against any assault or noxious conduct).

Investigation unit: Subsequent to getting the information as per the boundaries of defined QoS, investigating unit should look at received alerts. At that point, this data is handled by decision-making hub that can pass judgment in case these are bogus alerts by either utilizing information gathered from different sensors hubs or sending disaster management team to check condition.




Figure 3: Block diagram of the fire detection approach

3.1 Canadian approach

The Canadian assessment proposed computation of fire index as indicated by FWI (Fire Weather Index). This approach eradicates call for conveying every sensor collected record to the sink node, rather a couple of collected records are accounted for to decrease energy utilization. To assess the danger of rapidly spreading fire, the Canadian framework rate fire risk in terms of FWI. This framework comprises of 6 indices, Fine Fuel Moisture Code (FFMC), Duff Moisture Code (DMC), Drought code (DC), Initial Spread Index (ISI), Buildup Index (BUI), and finally Fire Weather Index (FWI), which represent impact of fuel dampness and wind on ablaze. The primary part is Fine Fuel Moisture Code (FFMC), which represent normal dampness content of garbage and different fuels. This code shows common facility of ignition and combustibility of fine fuels. Duff Moisture Code (DMC) stands for normal dampness content of organic layers present at moderate depth. This code shows fuel utilization at moderate layers. is Drought code (DC) is mathematical assessment of normal dampness content of deep organic layers. This code indicates occasional impacts of dryness on timberland fills and level of inactivity of fire at deep organic layers.

The secondary part is Initial Spread Index (ISI), which is a mathematical value of anticipated pace of fire spread. This index relies upon impact of wind and FFMC. Buildup Index (BUI) addresses entire accessible fuel for ignition. It is determined by consolidating DMC and DC. Utilizing BUI and ISI, at last FWI is acquired that is a numeric score of fire danger. It is considered as chief index of fire risk. This multitude of parts can be determined relying upon four basic climate parameters: temperature, relative moistness, wind speed, and 24h gathered precipitation.




Figure 1: Structure of FWI System

3.2 Korean approach

This approach is carried out utilizing Forest-fires Surveillance System (FFSS). FFSS senses climate and decides timberland fires hazard level using equation of Office of Forestry.

$$X = 6.87 + (0.64 X R) + (0.15 X E) + (1774.94/S)$$

Where E stands for Effective Humidity (%), S stands for Solar Radiation, R stands for Rain.

FFSS provides alert as displayed in diagram beneath:




Figure 2: Structure of FFSS

WSN comprises of sensor nodes that sense and convey temperature, stickiness and light information. Sink node is one of the sensor nodes of WSN. Sink-hub concentrates data packets from sensor hubs and forwards them to transceiver (gateway). Transceiver further transports packets from sink hub to middleware. Middleware accepts and processes packets from transceiver and provide their outcomes. Outcomes hold timberland fires hazard level. This level is determined by equation given by Office of Forestry .Thus, FFSS is a mechanized observation framework. Middleware keeps incoming packets in data set server. Middleware consists of certain parts that give constant diagram about incoming information on temperature, moistness, brightening and battery level. The manager can get sensor status data in light of chart and table.

Table 1: Hazard rating in view of FWI

Hazard Rating	Fire Index	Weather	Fire type
Low	0-4		Low flame fire
Medium	5-10		Low intensity fire
High	11-18		Moderate intensity fire
Very high	19-29		High intensity fire
Extreme	30+		Very high intensity fire

Table 2: Hazard rating in accordance with Korean Approach

X	Range of danger index	Hazard rating & flame color
10-12	80-100	Extreme (red)
13-14	60-79	High(yellow)
15	Under 60	Low(blue)

4.Fire Detection approaches

4.1 Canadian approach

This approach evaluates FWI index as explained below:




Figure 3: Flow chart of Canadian approach

Data packet configuration in Canadian approach is given below:

Board no. (8 bits)	Packet no. (8 bits)	Node no. (8 bits)	Reserved (8 bits)	H (8 bits)	T (8 bits)	FFMC (8 bits)	DMC (8 bits)	DC (8 bits)	FWI (8 bits)
------------------------------	-------------------------------	-----------------------------	-----------------------------	----------------------	----------------------	-------------------------	------------------------	-----------------------	------------------------

Where Board no.: sensor board identifier(MTS400 in our case)

Packet no.: package identifier

Node no.: sensor node identifier (TOS_LOCAL_ADRESS)

Reserved: Reserved field

H: Humidity

T: Temperature

FFMC, DMC, DC: intermediate indices determined on the basis of values of humidity, temperature, rain and wind speed

FWI: final index

4.2 Korean approach

Korean index is determined on the basis of values of humidity, light and rain. Korean algorithm is demonstrated below:




Figure 4: Flow chart of Korean approach

The data packet configuration has below mentioned fields:

Board no.	Packet no.	Node no.	Reserved	H	S	X
(8 bits)	(8 bits)	(8 bits)	(8 bits)	(8 bits)	(8 bits)	(8 bits)

5. Experimental results

Outcomes affirm the adjustment of Canadian framework to its neighboring environment. The accuracy of Korean approach is less contrasted with Canadian approach, since all outcomes acquired in Canadian technique by catching temperature and moistness prove exact results (FFMC, DC, DMC, FWI). In opposite, the quantities caught by Korean approach, particularly brilliance, are disturbed under same conditions, causing aggravation results for X parameter. In addition, Korean approach has higher energy consumption in contrast to Canadian approach. Hence it is proved that Canadian approach is better as far as energy utilization is concerned.




Figure 5: Graph showing energy consumption in Canadian and Korean methods




Figure 6: Graph showing time spent by CPU. Here, x- axis show Time (in seconds) and y- axis show Time (in terms of CPU cycles)

Figure above shows that Korean approach takes more CPU time than Canadian approach, yet source code of the last option includes a bigger number of guidelines than of Korean code (229 lines in Canadian code and 171 in Korean code). The postponement in Canadian graph above is because of the quantity of fields in data packet of each (7 fields in Korean and 10 in Canadian data packet) which means more data can be collected about the forest fire with the help of Canadian methodology which implies effective forest fire management can be done in this case, so Canadian system is better compared to Korean system

6. Conclusion

WSN innovation is an extremely encouraging green innovation for future for recognizing proficiently timberland fires in our country. Through genuine analyses, we end up in support of adequacy of Canadian methodology as far as energy proficiency and algorithmic intricacy is concerned contrasted with Korean method. Besides, more information recuperated by WSN about woods fire implies more powerful fire management by woodland specialists. Such WSN based frameworks shall resolve proficiently a few remarkable issues, for example, more accuracy of fire discovery and diminishing bogus alerts rate.

References:

1. ByoungChul Ko, JoonYoung Kwak, June Hyeok Hong and JaeYeal Nam (2011), "Current trend in natural disaster warning systems based on computer vision techniques," The First Asian Conference on Pattern Recognition, Beijing, China, pp. 1–5.
2. ByoungChul Ko and Sooyeong Kwak(2012):"Survey of computer vision based natural disaster warning system", in proceedings of SPIE
3. U. Ganesh, M. Anand, S. Arun, M. Dinesh, P. Gunaseelan, and R. Karthik(2013), "Forest fire detection using optimized solar-powered Zigbee wireless sensor networks," International Journal of Scientific and Engineering Research, vol. 4, pp. 586–596.
4. Michel Owayjan, George Freiha, Roger Achkar, Elie Abdo and Samy Mallah(2014):"Firoxio: Forest fire detection and alerting system", IEEE.
5. Mohamed Kameche, Haider Benzeniar, Ayhane Bey Benbouzid, Redha Amri and Nadir Bouanani(2014),"Disaster monitoring constellation using nanosatellites". Journal of Aerospace Technology and Management ,6(1), 93–100.
6. Kumarguru Poobalan and Siau-Chuin Liew(2015):"Fire detection algorithm using image processing techniques", International Conference on Artificial Intelligence and Computer Science.
7. Antonio Molina-Pico, David Cuesta-Frau, Alvaro Araujo, Javier Alejandro and Alba Rozas(2016):"Forest Monitoring and Wildland Early Fire Detection by a Hierarchical Wireless Sensor Network", Hindawi Publishing Corporation, Journal of Sensors, Vol. 2016, Article ID 8325845, 8 pages.
8. Sakib Abdullah, Sandor Bertalan, Stanislav Masar, Adem Coskun and Izzet Kale(2017):" A Wireless Sensor Network for Early Forest Fire Detection and Monitoring as a Decision Factor in the Context of a Complex Integrated Emergency Response System", IEEE.
9. Pradeep Kumar Singh and Amit Sharma(2018): "An insight to forest fire detection techniques using wireless sensor networks", IEEE.
10. Gaur, A.; Singh, A.; Kumar, A.; Kulkarni, K.S.; Lala, S.; Kapoor, K.; Srivastava, V.; Kumar, A.; Mukhopadhyay, S.C.(2019),"Fire sensing technologies: A review". IEEE Sensor Journal, vol.19(9), pp. 3191–3202.
11. Panagiotis Barmpoutis, Periklis Papaioannou, Kosmas Dimitropoulos and Nikos Grammalidis(2020):"A Review on Early Forest Fire Detection Systems Using Optical Remote Sensing", Sensors.
12. Beatriz Flãmia Azevedo, Thadeu Brito, Jose Lima and Ana I. Pereira(2021), "Optimum Sensors Allocation for a Forest Fires Monitoring System(2021)" Forests , 12, 453.